



# **ESCENE ES220**

**Product Catalog** 



ES220P is a popular type IP Phone in Sayhi phones series, with modern design, functional, practical and voice clarity characteristics. It accomplished the powerful telephony features by cooperating with the communications platform, such as call transfer, hotline, multi-party conferences, voice mail, interruption-free, etc.

### **Product Features**

#### Clear voice

ES220P series through the unique voice processing technology that enables voice calls for more clarity and realistic, and communication more fluent.

- Convenient and fast for Installation and maintenance
   Support HTTP/TFTP/Telnet/Phone setting
- Sophisticated functions Application
   Enterprise addresses book.
   private phone book application.
- Support Headset interface
   Suitable for call center applications.
- Support POE and AC adapter power supply
- Support HTTP/TFTP/FTP Auto-provision/TR069 for upgrade software



## **Technical Specification**

Item	ES320
Screen	grayscale LCD with background light
	128*32 character
Language	Support Multi-Module
Line	2
Function Keys	6 Navigation keys (Arrow button, OK button, C button) Volume button(multiplex up and down keys) Hands-free Mute Headset Message Menu Hold Redial Conference Transfer
VoIP Protocol	SIP 2.0
Network Protocol	HTTP, BOOTP, FTP, TFTP, IEEE 802.1Q, *IEEE 802.1X
Codec	G.723.1, G.729 A/B, G.711 A/U, G.722
QoS	TOS, Jiffer Buffer, VAD, CNG, G.168 (32ms)
Network	2×RJ45 10/100M Ethernet Interfaces (LAN/PC) IP Assignment: static IP, DHCP, PPPoE DNS Client, VPN(L2TP), VLAN/QoS
Speech	HD Voice: HD Codec/Handset/Speaker(Full-duplex) Handle, Headset and Hands-free model available Support call centre by headsets Separated 9 Level Volume Adjustment
Call Processing	Always Forward, Busy Forward, No-answer Forward Hotline line (Immediately/Delay) Call Waiting, Call Queuing Call Forward, Call Transfer, Call Holding, Call Pickup, *Callback Redial Phone directory speed dial, Call record direct dial 3-way conference DnD, *Blacklist, SMS Voice mail, Voice Prompt, Voice Message
Application	Enterprise phone directory XML Phonebook Private phone directory
Security	Login the website by password Signaling encryption Media encryption



Management	Upgrade: HTTP/TFTP/FTP Auto-provision/TR069
	Configurations: Phone/Http/Auto provision/TR069
	Debug: Telnet/Phone/Web
Power Supply	Power adapter:AC100~240V input and DC 5V/1A output
	PoE(IEEE 802.af)
Specification	Storage Temperature: 0°C ~ 60°C
	Operating Humidity: 10%~90%
	Size: 335mm x 219mm x 68mm
	Net weight: 1.07kg
Package Features	Qty/CTN: 10 PCS
	N.W/CTN: 10.7kg
	G.W/CTN: 11.2kg
	Measurement: 0.055CBM
	Carton Meas: 460mm x 350mm x 355mm
Certifications	CE, FCC, RoHS

#### **Contact Information**

In China:

GUANGZHOU ESCENE COMMUNICATION CO.,LTD.

Web: http://www.escene.cn Tel: (+86)20-28096798 Fax: (+86)20-28096786

Address: Floor 4 Building C YueAn Industrial Park No.54 Huangcun Road Tianhe District Guangzhou, China

In Iran :

Saean Ertebat Co.

Web: <a href="http://www.senatelecom.com">http://www.senatelecom.com</a>

Tel: (+98)21-88316704

Fax: (+98)21-88316718 Address: Suite# 104, No. 34, Uraman St., Motahari St., Tehran, Iran